

Tubería Cuadrada				
Descripcion	pulg	calibre	Lingitud (metros)	Kilogramo x metro
C-050	.500"	22	6	0,27
		20	6	0,32
		18	6	0,41
		16	6	0,49
C-062	.625"	20	6	0,41
		18	6	0,53
		16	6	0,64
C-075	.750"	22	6	0,43
		20	6	0,5
		18	6	0,65
		16	6	0,79
		14	6	0,95
C-087	.875"	20	6	0,59
		18	6	0,77
C-100	1.000"	20	6	0,69
		18	6	0,89
		16	6	1,09
		14	6	1,33
		13	6	1,55
		12	6	1,76
		11	6	1,95
		10	6	2,13
C-125	1.250"	20	6	0,87
		18	6	1,14
		16	6	1,4
		14	6	1,71
		12	6	2,29
		11	6	2,26
		10	6	2,81
C-150	1.500"	20	6	1,05
		18	6	1,38
		16	6	1,7
		14	6	2,09
		12	6	2,82
		11	6	3,16
		10	6	3,49
		9	6	3,8
C-175	1.750"	16	6	2
		14	6	2,47
		11	6	3,77
C-200	2.000"	20	6	1,41
		18	6	1,86
		16	6	2,31
		14	6	2,84
		12	6	3,88
		11	6	4,38

		10	6	4,85
		9	6	5,32
		3/16	6	6,44
		1/4	6	8,06
C-225	2.250"	16	6	2,61
		14	6	3,22
C-250	2.500"	16	6	2,91
		14	6	3,6
		13	6	4,28
		12	6	4,94
		11	6	5,59
		10	6	6,22
		9	6	6,84
		3/16	6	8,34
		1/4	6	10,59
C-300	3.000"	14	6	4,36
		13	6	5,19
		12	6	6
		11	6	6,8
		10	6	7,58
		9	6	8,35
		3/16	6	10,24
		1/4	6	13,13
C-350	3.500"	14	6	5,12
		11	6	8,01
		9	6	9,87
		3/16	6	12,14
		1/4	6	15,67
C-400	4.000"	14	6	5,88
		11	6	9,23
		10	6	10,31
		9	6	11,39
		3/16	6	14,04
		1/4	6	18,2
C-450	4.500"	11	6	10,44
		3/16	6	15,94
		1/4	6	20,74
C-500	5.000"	3/16	6	17,85
		1/4	6	23,27
C-600	6.000"	3/16	6	21,65
		1/4	6	28,35